











**Table 2
Identification and Illustration of Displays**

Column 1	Column 2	Column 3	Column 4	Column 5
<i>Display</i>	<i>Telltale Color</i>	<i>Identifying Words or Abbreviation</i>	<i>Identifying Symbol</i>	<i>Illumination</i>
Turn Signal Telltale	Green	Also See FMVSS 108	 1,5	_____
Hazard Warning Telltale		Also See FMVSS 108	 2,5	_____
Seat Belt Telltale	_____ 4	Fasten Belts or Fasten Seat Belts Also See FMVSS 208	 or 	_____
<u>Fuel Level</u> Telltale		Fuel	 or 	_____
Gauge	_____			Yes
<u>Oil Pressure</u> Telltale		Oil		_____
Gauge	_____			Yes
<u>Coolant Temperature</u> Telltale		Temp		_____
Gauge	_____			Yes
<u>Electrical Charge</u> Telltale		Volts, Charge or Amp		_____
Gauge	_____			Yes
Highbeam Telltale	Blue or Green 3	Also See FMVSS 108	 5	_____
Brake System 8	Red 3	Brake, Also see FMVSS 105 and 135	_____	_____

1. The pair of arrows is a single symbol. When the indicator for left and right turn operate independently, however, the two arrows will be considered separate symbols and may be spaced accordingly.
2. Not required when arrows of turn signal telltales that otherwise operate independently flash simultaneously as hazard warning telltale.
3. Red can be red-orange. Blue can be blue-green.
4. The color of the telltale required by S4.5.3.3 of Standard No. 208 is red; the color of the telltale required by S7.3 of Standard No. 208 is not specified.
5. Framed areas may be filled.
6. In the case where a single telltale indicates more than one brake system condition, the word for Brake System shall be used.